

DEXRON® Achsial-Rillen-Kugal-Lager – Modified PV 1454
Report Form
Form 1
Version

Formulation Code							
Formulation Code							
SPONID	SponsorCode	Modification	Blend	Count	TestType	Lab	Instrument

Test Identification			
Sponsor			
Sponsor In-House Number			
Lab In-House Number			
Alternate Code			
Test Number ^A			
Instrument		Run Number	
Start Date		Start Time	
EOT Date		EOT Time	

^ATest Number = Instrument – Run Number

Test Validity Statement	
This test has been conducted in a valid manner – YES or NO	
Test Laboratory	
Signature	
Typed Name	
Title	

DEXRON® Achsial-Rillen-Kugal-Lager – Modified PV 1454

Pass/Fail Results

Form 2

Formulation Code	
Test Number	

Pass/Fail Results		
Parameter	Unit	Result
Average Steady-State Temperature	°C	

Test Operating Conditions	
Rotation Speed, rpm	
Oil Volume, ml	
Load, N	
Test Duration, min	

Comments

DEXRON® Achsial-Rillen-Kugal-Lager – Modified PV 1454

Test Data

Form 3

Formulation Code	
Test Number	

Test Results			
Test Run	Temperature (°C)		
	Ambient*	Test Fluid*	Steady-State**
Run 1			
Run 2			
Run 3			
Average			
Standard Deviation			

* Temperature at maximum speed during last minute of operation, as defined by GM

** $T_{\text{steady-state}} = 30^{\circ}\text{C} - T_{\text{ambient}} + T_{\text{oil sump}}$ (according to PV 1454)

DEXRON® Achsial-Rillen-Kugal-Lager – Modified PV 1454

Run 1 Plot

Form 4

Formulation Code	
Test Number	

DEXRON® Achsial-Rillen-Kugal-Lager – Modified PV 1454

Run 2 Plot

Form 5

Formulation Code	
Test Number	

DEXRON® Achsial-Rillen-Kugal-Lager – Modified PV 1454

Run 3 Plot

Form 6

Formulation Code	
Test Number	

DEXRON® Achsial-Rillen-Kugal-Lager – Modified PV 1454
Test Fluid Temperature Plot
Form 7

Formulation Code	
Test Number	