

**DEXRON® Elastomer Compatibility Test  
Report Form  
Form 1  
Version**

Formulation Code							
Formulation Code							
SPONID	SponsorCode	Modification	Blend	Count	Method <sup>A</sup>	Lab	Bath

Blended Sample Testing Information <sup>B</sup>		
Candidate Percentage		Other Percentage
Other Fluid ID		

<sup>B</sup>If not a Blended Sample then report 100% Candidate Percentage, 0% Other Percentage, and "None" for Blend Fluid ID.

Test Identification			
Sponsor			
Sponsor In-House Number			
Lab In-House Number			
Alternate Code			
Test Number <sup>C</sup>			
Bath		Run Number	
Start Date		Start Time	
EOT Date		EOT Time	
Test Condition Designation <sup>A</sup>			
Elastomer Type <sup>D</sup>		Elastomer Batch	

<sup>B</sup> Bath-Run Number

<sup>A</sup>Method suffix values and Test Condition Designation values are shown the table below:

Method Suffix	Test Condition Designation	Description
A	D168	Run according to DEXRON HP Appendix B (Test temp. =150 °C, Immersion time=168 h)
B	D504	Run according to DEXRON VI Appendix B (Test temp. =150 °C, Immersion time=504 h)
C	D1008	Run according to DEXRON HP Appendix B (Test temp. =150 °C, Immersion time=1008 h)

<sup>D</sup>Elastomer Type = FKM2 or FKM3 or FKM5 or AEM2 or AEM3 or ACM1 or ACM2 or NBR1 or HNBR1

Test Validity Statement	
This test has been conducted in a valid manner – YES or NO	
Test	
Signature	
Typed Name	
Title	

Test Information			
Test Length (h)		Test Temperature (°C)	

**DEXRON® Elastomer Compatibility Test  
Pass/Fail Results  
Form 2**

Formulation Code	
Test Number	

<b>Pass/Fail Results</b>			
<b>Test Parameter <sup>E</sup></b>	<b>Units</b>	<b>Reference Oil <sup>E</sup></b>	<b>Candidate Oil <sup>E</sup></b>
Volume Change	%		
Hardness Change	Shore-A Points		
Tensile Strength Change	%		
Elongation Change at Rupture	%		
Stress Change @ 50% Elongation	%		
180° Bend Test	Pass or Fail		

<sup>E</sup> Only if required by test method. Otherwise report NA.

<b>Test Comments</b>