

**DEXRON® GM Three (3) Day Wear Test
Report Form
Form 1
Version**

| Formulation Code | | | | | | | |
|------------------|-------------|--------------|-------|--------|-------|-----|------------|
| Formulation Code | | | | | | | |
| SID | SponsorCode | Modification | Blend | Method | Count | Lab | Instrument |
| | | | | | | | |

| Blended Sample Testing Information ^A | | | |
|---|--|------------------|--|
| Candidate Percentage | | Other Percentage | |
| Other Fluid ID | | | |

^A If not a Blended Sample then report 100% Candidate Percentage, 0% Other Percentage, and "None" for Blend Fluid ID.

| Test Identification | | | |
|--------------------------|--|------------|--|
| Sponsor | | | |
| Sponsor In-House Number | | | |
| Lab In-House Number | | | |
| Alternate Code | | | |
| Test Number ^B | | | |
| Instrument | | Run Number | |
| Start Date | | Start Time | |
| EOT Date | | EOT Time | |

^B Test Number = Instrument – Run Number

| Test Validity Statement | |
|--|--|
| This test has been conducted in a valid manner – YES or NO | |
| | |
| Test Laboratory | |
| Signature | |
| Typed Name | |
| Title | |

**DEXRON® GM Three (3) Day Wear Test
Test Operational Details & Comments
Form 2**

| | |
|------------------|--|
| Formulation Code | |
| Test Number | |

| Test Fluid Condition before Testing | |
|--|--|
| Test Fluid Condition ^A | |
| <i>^A Fluid Condition Values</i> | <i>Description</i> |
| <i>NEW</i> | <i>New Fluid</i> |
| <i>H2O</i> | <i>New Fluid treated with 1000 ppm Water, per GM procedure</i> |

| Test Operational Details | |
|------------------------------------|--|
| Clutch Plate Type | |
| Friction Material ID, mm | |
| Friction Material OD, mm | |
| Groove % | |
| Groove Pattern | |
| Effective Friction Radius, mm | |
| Apply Piston Area, mm ² | |
| Friction Material Type | |
| Friction Material Batch | |
| Steel Separator Type | |
| Steel Separator Batch | |
| Test Machine Type | |

| Comments |
|-----------------|
| |
| |
| |
| |
| |

**DEXRON® GM Three (3) Day Wear Test
Clutch Pack Plate Thickness Measurements
Form 3**

| | |
|------------------|--|
| Formulation Code | |
| Test Number | |

| Pre Test (New), mm | | | |
|---------------------------|-------------|------------|---------------|
| Position | Front Steel | Rear Steel | Friction Disc |
| 12:00 | | | |
| 3:00 | | | |
| 6:00 | | | |
| 9:00 | | | |
| Average | | | |

| Post Break In, mm | | | |
|--------------------------|-------------|------------|---------------|
| Position | Front Steel | Rear Steel | Friction Disc |
| 12:00 | | | |
| 3:00 | | | |
| 6:00 | | | |
| 9:00 | | | |
| Average | | | |

| Post Test, mm | | | |
|----------------------|-------------|------------|---------------|
| Position | Front Steel | Rear Steel | Friction Disc |
| 12:00 | | | |
| 3:00 | | | |
| 6:00 | | | |
| 9:00 | | | |
| Average | | | |

| (Pre Test) – (Post Break In), mm | | | |
|---|-------------|------------|---------------|
| Position | Front Steel | Rear Steel | Friction Disc |
| 12:00 | | | |
| 3:00 | | | |
| 6:00 | | | |
| 9:00 | | | |
| Average | | | |

| (Post Break In) - (Post Test), mm | | | |
|--|-------------|------------|---------------|
| Position | Front Steel | Rear Steel | Friction Disc |
| 12:00 | | | |
| 3:00 | | | |
| 6:00 | | | |
| 9:00 | | | |
| Average | | | |

| (Pre Test) - (Post Test), mm | | | |
|-------------------------------------|-------------|------------|---------------|
| Position | Front Steel | Rear Steel | Friction Disc |
| 12:00 | | | |
| 3:00 | | | |
| 6:00 | | | |
| 9:00 | | | |
| Average | | | |

**DEXRON® GM Three (3) Day Wear Test
Test Report Placeholder Form
Form 4**

| | |
|------------------|--|
| Formulation Code | |
| Test Number | |

Append the complete test report PDF to these forms, in place of this page.