

**DEXRON® Tapered Roller Bearing Shear Stability – CEC L-45-99 Modified
Report Forms
Form 1**

Formulation Code							
Formulation Code							
SPONID	SponsorCode	Modification	Blend	Count	TestType	Lab	Test Rig

Test Identification			
Sponsor			
Sponsor In-House Number			
Lab In-House Number			
Alternate Code			
Test Number ^A			
Test Rig		Run Number	
Start Date		Start Time	
EOT Date		EOT Time	

^ATest Number = Test Rig– Run Number

Test Validity Statement	
This test has been conducted in a valid manner – YES or NO	
Test Laboratory	
Signature	
Typed Name	
Title	

**DEXRON® Tapered Roller Bearing Shear Stability – CEC L-45-99 Modified
Pass/Fail Results
Form 2**

Formulation Code	
Test Number	

Pass/Fail Result	
EOT Kinematic Viscosity @ 100°C - cSt	
EOT Kinematic Viscosity Change @ EOT - %	
(Base Oil Viscosity + EOT Viscosity)/2 - cSt	

Test Conditions	
Revolutions	
Test Length - h	
Test Fluid Temperature - °C	

Viscosity Measurements			
	Viscosity - cSt	Delta - cSt	Change - %
Initial Kinematic Viscosity @ 100°C			
EOT Kinematic Viscosity @ 100°C			
Base Oil Viscosity @ 100°C			

Comments