

**DEXRON® Tapered Roller Bearing Shear Stability – CEC L-45-99 Modified  
Report Forms  
Form 1**

<b>Formulation Code</b>							
Formulation Code							
SPONID	SponsorCode	Modification	Blend	Count	TestType	Lab	Test Rig

<b>Test Identification</b>			
Sponsor			
Sponsor In-House Number			
Lab In-House Number			
Alternate Code			
Test Number <sup>A</sup>			
Test Rig		Run Number	
Start Date		Start Time	
EOT Date		EOT Time	

<sup>A</sup>Test Number = Test Rig– Run Number

<b>Test Validity Statement</b>	
This test has been conducted in a valid manner – YES or NO	
Test Laboratory	
Signature	
Typed Name	
Title	

**DEXRON® Tapered Roller Bearing Shear Stability – CEC L-45-99 Modified  
Pass/Fail Results  
Form 2**

Formulation Code	
Test Number	

<b>Pass/Fail Result</b>	
EOT Kinematic Viscosity @ 100°C - cSt	
EOT Kinematic Viscosity Change @ EOT - %	
(Base Oil Viscosity + EOT Viscosity)/2 - cSt	

<b>Test Conditions</b>	
Revolutions	
Test Length - h	
Test Fluid Temperature - °C	

<b>Viscosity Measurements</b>			
	Viscosity - cSt	Delta - cSt	Change - %
Initial Kinematic Viscosity @ 100°C			
EOT Kinematic Viscosity @ 100°C			
Base Oil Viscosity @ 100°C			

<b>Comments</b>