

**DEXRON® Tapered Roller Bearing Shear Stability – CEC L-45-99 Modified  
Report Forms  
Form 1**

Formulation Code							
Formulation Code							
SPONID	SponsorCode	Modification	Blend	Count	Method	Lab	Test Rig

Blended Sample Testing Information <sup>A</sup>			
Candidate Percentage		Other Percentage	
Other Fluid ID			

<sup>A</sup> If not a Blended Sample then report 100% Candidate Percentage, 0% Other Percentage, and “None” for Blend Fluid ID.

Test Identification			
Sponsor			
Sponsor In-House Number			
Lab In-House Number			
Alternate Code			
Test Number <sup>B</sup>			
Test Rig		Run Number	
Start Date		Start Time	
EOT Date		EOT Time	

<sup>B</sup> Test Number = Test Rig– Run Number

Test Validity Statement	
This test has been conducted in a valid manner – YES or NO	
Test Laboratory	
Signature	
Typed Name	
Title	

**DEXRON® Tapered Roller Bearing Shear Stability – CEC L-45-99 Modified  
Pass/Fail Results  
Form 2**

Formulation Code	
Test Number	

<b>Pass/Fail Result</b>	
EOT Kinematic Viscosity @ 100°C - cSt	
EOT Kinematic Viscosity Change @ EOT - %	
(Base Oil Viscosity + EOT Viscosity)/2 - cSt	

<b>Test Conditions</b>	
Revolutions	
Test Length - h	
Test Fluid Temperature - °C	

<b>Viscosity Measurements</b>			
	Viscosity - cSt	Delta - cSt	Change - %
Initial Kinematic Viscosity @ 100°C			
EOT Kinematic Viscosity @ 100°C			
Base Oil Viscosity @ 100°C			

<b>Comments</b>